TBR TIRES



GM138

▸ OFF ROAD ▸ MIXED ROAD ▸ MINING





PATTERN CHARACTERISTIC

- Buttress Shoulder,Helps resist wear in high scrub applications;
- Full-depth sipes,Offer exceptional traction throughout the usable tire life;
- Full-width protector ply,Helps protect the working plies from bruises and penetration,and helps lower down time.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	16	M	8.25	1054	279	146/143	830	3000	2725	16.0
12R22.5	18	M	9.00	1085	300	152/149	930	3550	3250	16.0
315/80R22.5	18	M	9.00	1076	312	154/151	830	3750	3450	18.0
315/80R22.5	20	M	9.00	1076	312	156/150	850	4000	3350	18.0

GM158

▸ HIGHWAY ▸ URBAN





PATTERN CHARACTERISTIC

- The superior drive tyre for long distance highway and regional use;
- The Convex Block design provide excellent wet and dry manoeuvrability;
- Deep block tread provide minimum wear and long original tread life;
- Wide base and deep groove provide good resistance to irregular wear & heat generation.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11.00R20	18	K	8.00	1085	293	152/149	930	3550	3250	16.5



GM168

▸ HIGHWAY ▸ URBAN



PATTERN CHARACTERISTIC

- Super highway performance &handling;
- Circumferential grooves enhance wet traction;
- High-technology belt system offers ride comfort;
- Fuel-efficient casing insures fuel economy.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11.00R20	18	K	8.00	1083	288	152/149	930	3550	3250	16.5



GM512

▸ HIGHWAY ▸ ON/OFF ▸ URBAN



PATTERN CHARACTERISTIC

- Unique belt structure,Offers toughness to help deliver long tire life;
- Stable tread with cool running compound,helps generate reduced squirm and lower heat for improved handling and durability;
- Barrel-shaped footprint and five-rib design,Offer even wear, many miles to removal and a low cost per mile;
- Multi-siping,helps deliver dependable grip and long,even wear.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
215/75R17.5	16	M	6.00	768	211	126/124	700	1700	1600	12.0
215/75R17.5	18	J	6.00	773	211	135/133	700	1700	1600	12.0
235/75R17.5	16	M	6.75	793	233	132/130	775	2000	1900	12.0
235/75R17.5	18	J	6.75	798	233	143/141	775	2000	1900	12.0
225/70R19.5	14	M	6.75	814	226	128/126	760	1800	1700	12.0
245/70R19.5	16	M	7.50	841	248	136/134	825	2240	2120	12.0
265/70R19.5	16	M	7.50	869	262	140/138	775	2500	2360	12.0
275/70R22.5	16	M	8.25	952	276	148/145	760	2800	2575	14.0
275/70R22.5	18	M	8.25	952	276	144/141	850	3150	2900	14.0
285/75R24.5	16	M	8.25	1049	283	146/143	830	3000	2725	14.0
295/75R22.5	16	M	9.00	1011	298	146/143	830	3000	2725	14.0
11R22.5	14	M	8.25	1048	279	144/142	720	2800	2650	14.0
11R22.5	16	M	8.25	1048	279	146/143	830	3000	2725	14.0
11R24.5	14	M	8.25	1098	279	146/143	720	3000	2725	14.0
11R24.5	16	M	8.25	1098	279	149/146	830	3250	3000	14.0



SmartWay

GM522

▸ HIGHWAY ▸ ON/OFF ▸ URBAN



PATTERN CHARACTERISTIC

- Tough blocks,Provide excellent traction and off-road performance throughout the life of the tyre;
- Special pattern design,Effectively improve the self-cleaning performance;
- Deep grooves,Provide long tread life;
- Strong,solid shoulders,Give excellent stability and handling.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
285/75R24.5	16	M	8.25	1063	283	146/143	830	3000	2725	21.0
295/75R22.5	16	M	9.00	1025	298	146/143	830	3000	2725	21.0
11R22.5	14	M	8.25	1062	279	144/142	720	2800	2650	21.0
11R22.5	16	M	8.25	1062	279	146/143	830	3000	2725	21.0
11R24.5	14	M	8.25	1112	279	146/143	720	3000	2725	21.0
11R24.5	16	M	8.25	1112	279	149/146	830	3250	3000	21.0



GM562

▸ HIGHWAY ▸ ON/OFF ▸ URBAN

PATTERN CHARACTERISTIC

- Unique belt structure,Offers toughness to help deliver long tire life;
- Stable tread with cool running compound,helps generate reduced squirm and lower heat for improved handling and durability;
- Barrel-shaped footprint and five-rib design,Offer even wear, many miles to removal and a low cost per mile;
- Multi-siping,helps deliver dependable grip and long, even wear.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	16	M	8.25	1050	279	146/143	830	3000	2725	15.0
12R22.5	18	M	9.00	1074	300	152/149	930	3550	3250	16.5
275/80R22.5	16	M	8.25	1012	276	149/146	850	3250	3000	14.0
295/80R22.5	18	M	9.00	1043	298	152/149	900	3550	3250	15.0
315/70R22.5	18	M	9.00	1012	312	152/148	830	3550	3150	15.0
315/80R22.5	20	M	9.00	1079	313	156/150	850	4000	3350	16.0



SmartWay



GM563

▸ HIGHWAY



PATTERN CHARACTERISTIC

- The pattern provides good pulling force;
- Applicable for high speed and long mileage.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
12R22.5	18	M	9.00	1079	300	152/149	930	3550	3250	19.0



GM565

▸ HIGHWAY ▸ REGIONAL



PATTERN CHARACTERISTIC

- Wide and deep tread design provide extended tread life;
- Special tread pattern delivers a smooth and consistent wear;
- Uniform blog & lug design provide efficient traction on wet and dry roads.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
12R22.5	18	M	9.00	1090	300	152/149	930	3550	3250	21.5



GM566

▸ HIGHWAY ▸ ON/OFF ▸ URBAN



PATTERN CHARACTERISTIC

- Unique belt structure,Offers toughness to help deliver long tire life;
- Stable tread with cool running compound,helps generate reduced squirm and lower heat for improved handling and durability;
- Barrel-shaped footprint and five-rib design,Offer even wear, many miles to removal and a low cost per mile;
- Multi-siping,helps deliver dependable grip and long, even wear.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
385/65R22.5	20	K	11.75	1066	389	160	900	4500	--	15.0



GM578

▸ HIGHWAY ▸ ON/OFF ▸ URBAN



PATTERN CHARACTERISTIC

- The Convex Block design,Excellent wet and dry manoeuvrability;
- Deep block tread,Minimum wear and long original tread life;
- Wide base and deep groove,Good resistance to irregular wear and resists heat generation in casing.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	16	M	8.25	1060	279	146/143	830	3000	2725	20.0
12R22.5	18	M	9.00	1081	300	152/149	930	3550	3250	20.0
215/75R17.5	16	M	6.00	768	211	126/124	700	1700	1600	15.0
215/75R17.5	18	J	6.00	773	211	135/133	700	1700	1600	15.0
235/75R17.5	16	M	6.75	793	233	132/130	775	2000	1900	15.0
235/75R17.5	18	J	6.75	798	233	143/141	775	2000	1900	15.0
225/70R19.5	14	M	6.75	819	226	128/126	760	1800	1700	15.0
245/70R19.5	16	M	7.50	846	248	136/134	825	2240	2120	15.0
265/70R19.5	16	M	7.50	874	262	140/138	775	2500	2360	15.0
275/80R22.5	16	M	8.25	1021	276	149/146	850	3250	3000	19.0
295/80R22.5	18	M	9.00	1053	298	152/149	900	3550	3250	20.0
315/70R22.5	18	M	9.00	1022	312	152/148	830	3550	3150	20.0
315/80R22.5	18	M	9.00	1087	313	154/151	830	3750	3450	20.0
315/80R22.5	20	M	9.00	1087	313	156/150	850	4000	3350	20.0





GM582

▸ ON/OFF ▸ MIXED ROAD





PATTERN CHARACTERISTIC

- Buttress Shoulder,Helps resist wear in high scrub applications;
- Full-depth sipes,Offer exceptional traction throughout the usable tire life;
- Full-width protector ply,Helps protect the working plies from bruises and penetration,and helps lower down time.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
12.00R24	20	K	8.50	1214	315	160/157	900	4500	4125	14.5

GM583

▸ ON/OFF ▸ MIXED ROAD





PATTERN CHARACTERISTIC

- Buttress Shoulder,Helps resist wear in high scrub applications;
- Full-depth sipes,Offer exceptional traction throughout the usable tire life;
- Full-width protector ply,Helps protect the working plies from bruises and penetration,and helps lower down time.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11.00R20	18	L	8.00	1084	293	152/149	930	3550	3250	16.5
12.00R20	20	L	8.50	1131	315	156/153	900	4000	3650	18.0

GM585

▸ OFF ROAD ▸ MINING ▸ MIXED ROAD





PATTERN CHARACTERISTIC

- Designed with block tread for off road with extra deep tread depth;
- Excellent structure ensures wear resistance and heavy loads;
- Long mileage with strong tractions.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11.00R20	18	E	8.00	1097	293	152/149	930	3550	3250	23.0
12.00R20	20	E	8.50	1124	315	156/153	900	4000	3650	24.0

GM586

▸ OFF ROAD ▸ MINING ▸ MIXED ROAD





PATTERN CHARACTERISTIC

- Buttress Shoulder,Helps resist wear in high scrub applications;
- Full-depth sipes,Offer exceptional traction throughout the usable tire life;
- Full-width protector ply,Helps protect the working plies from bruises and penetration,and helps lower down time.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11.00R20	18	E	8.00	1100	293	152/149	930	3550	3250	24.5
12.00R20	20	E	8.50	1134	315	156/153	900	4000	3650	25.5



GM628

▸ OFF ROAD ▸ MINING ▸ MIXED ROAD



PATTERN CHARACTERISTIC

- Deep tread makes aggressive traction and long original mileage;
- Self-cleaning tread with high traction and stone rejection performance;
- Special tread compounds resistant to cuts, chips, tearing and irregular wear;
- Wide base design ensures higher payload and outstanding flotation.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11.00R20	18	D	8.00	1099	288	152/149	930	3550	3250	23.5
12.00R20	20	D	8.50	1132	310	156/153	900	4000	3650	24.5
295/80R22.5	18	M	9.00	1053	292	152/149	900	3550	3250	21.0



GM658

▸ MINING ▸ OFF ROAD



PATTERN CHARACTERISTIC

- Heavy tread blocks,ultra deep tread design,to provide a strong driving force,with strong adhesion;
- Tire using structure,with excellent bearing capacity high running life,resistance to puncture.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
10.00R20	18	D	7.50	1062	276	149/146	930	3250	3000	22.5
11.00R20	18	D	8.00	1096	288	152/149	930	3550	3250	23.5
12.00R20	20	D	8.50	1133	310	156/153	900	4000	3650	24.5



GM698

▸ HIGHWAY ▸ URBAN



PATTERN CHARACTERISTIC


- The superior drive tyre for long distance highway and regional use;
- The Convex Block design provide excellent wet and dry manoeuvrability;
- Deep block tread provide minimum wear and long original tread life;
- Wide base and deep groove provide good resistance to irregular wear and heat generation.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
385/65R22.5	20	K	11.75	1070	384	160	900	4500	--	16.0



GM712

▸ HIGHWAY ▸ REGIONAL



PATTERN CHARACTERISTIC

- Special rubber compounds enhance traction and treadwear;
- Circumferential grooves enhance wet traction;
- High-technology belt system offers ride comfort;
- Fuel-efficient casing insures fuel economy.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
8.25R16	16	K	6.50H	855	235	128/124	770	1800	1600	14.0
11R22.5	16	M	8.25	1048	273	146/143	830	3000	2725	15.0
12R22.5	18	M	9.00	1081	292.1	152/149	930	3550	3250	15.0
295/80R22.5	18	M	9.00	1041	292	152/149	900	3550	3250	15.0
315/70R22.5	18	M	9.00	1009	310	151/148	830	3450	3150	14.5
315/80R22.5	18	M	9.00	1078	310	154/151	830	3750	3450	15.0
315/80R22.5	20	L	9.00	1078	310	156/150	850	4000	3350	15.0





GM788

▸ HIGHWAY ▸ REGIONAL



PATTERN CHARACTERISTIC

•Good sideslip and mud slip resistance;
•Suitable for guiding and all use.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
295/80R22.5	18	M	9.00	1047	292	152/149	900	3550	3250	18.0



GM826

▸ MIXED ROAD ▸ OFF ROAD



PATTERN CHARACTERISTIC

•Superior in braking and driving performance;
•High wear resistance;
•Super adhesion performance;
•Good loading capacity.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	16	M	8.25	1058	273	146/143	830	3000	2725	22.5
12.00R24	20	K	8.50	1226	315	160/157	900	4500	4125	24.0



GM836

▸ ON/OFF ▸ SNOW



PATTERN CHARACTERISTIC

•Designed with block tread for an the road use specially;
•Open shoulder design provides good traction and long mileage on all road conditions;
•Applicable for high speed and lower noise.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
315/80R22.5	20	L	9.00	1087	310	156/150	850	4000	3350	20.0



GM859

▸ HIGHWAY ▸ ON/OFF



PATTERN CHARACTERISTIC

•Buttress Shoulder,Helps resist wear in high scrub applications;
•Full-depth sipes,Offer exceptional traction throughout the usable tire life;
•Full-width protector ply,Helps protect the working plies from bruises and penetration,and helps lower down time.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
12.00R24	18	K	8.50	1215	316	150/146	830	4250	3875	16.0
12.00R24	20	K	8.50	1215	316	160/157	900	4500	4125	16.0





GM869

▸ OFF ROAD ▸ MIXED ROAD ▸ MINING



PATTERN CHARACTERISTIC

- Special rubber compound designed for varied applications;
- Improved damage resistance to the crown and sidewalls;
- Deep and wide tread pattern provide excellent traction on loose ground;
- Reinforced crown and sidewalls provide increased casing life even with maximum loading.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
10.00R20	18	K	7.50	1054	278	149/146	930	3250	3000	20.0
11.00R20	18	L	8.00	1085	293	152/149	930	3550	3250	22.0
12.00R20	18	D	8.50	1125	315	154/151	830	3750	3450	21.5
12.00R20	20	L	8.50	1125	315	156/153	900	4000	3650	21.0
12R22.5	18	M	9.00	1089	292	152/149	930	3550	3250	19.0



GM901

▸ HIGHWAY ▸ ON/OFF ▸ URBAN



PATTERN CHARACTERISTIC

- Specific tread compound enable lower heating,wear resistance and fuel economy;
- Extended road mileage;
- Zigzag grooves angle resist stone retention and drilling;
- Ultra-high tire bead structure ensure excellent high speed and durability;
- Lateral block shoulder water helps draining wet skid resistance and soft soil mobility.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
7.00R16LT	14	K	5.50F	770	200	118/114	770	1320	1180	12.0
7.50R16LT	14	K	6.00G	803	215	122/118	770	1500	1320	12.0
8.25R16	16	L	6.5H	855	235	128/124	770	1800	1600	14.0
8.25R20	16	K	6.50	974	236	139/137	930	2430	2300	14.0
9.00R20	16	H	7.00	1018	260	144/142	900	2800	2650	15.5
10.00R20	18	K	7.50	1054	278	149/146	930	3250	3000	16.0
11.00R20	18	K	8.00	1085	293	152/149	930	3550	3250	17.0
12.00R20	18	L	8.50	1125	315	154/151	830	3750	3450	17.5
12.00R20	20	L	8.50	1122	310	156/153	900	4000	3650	17.5
12.00R24	20	K	8.50	1226	315	160/157	900	4500	4125	16.0
11R22.5	16	M	8.25	1047	273	146/143	830	3000	2725	15.0
11R22.5	18	M	8.25	1050	279	146/143	850	3150	2900	15.0
11R24.5	16	L	8.25	1098	279	149/146	830	3250	3000	14.5
12R22.5	18	M	9.00	1084	300	152/149	930	3550	3250	16.0
13R22.5	18	M	9.75	1120	315	154/151	830	4000	3550	16.0
315/80R22.5	20	L	9.00	1080	310	156/150	850	4000	3550	16.0

GM902

▸ HIGHWAY ▸ REGIONAL



PATTERN CHARACTERISTIC

- Good sideslip and mud slip resistance;
- Suitable for guiding and all use.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11.00R20	18	L	8.00	1085	293	152/149	930	3550	3250	16.5



GM903

▸ HIGHWAY ▸ ON/OFF ▸ URBAN



PATTERN CHARACTERISTIC

- Specific tread compound enable lower heating,wear resistance and fuel economy;
- Extended road mileage;
- Ultra-high tire bead structure ensure excellent high speed and durability.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
10.00R20	18	K	7.50	1054	278	149/146	930	3250	3000	16.0
11.00R20	18	L	8.00	1085	293	152/149	930	3550	3250	16.5
12.00R20	18	L	8.50	1125	315	154/151	830	4000	3650	17.0
12.00R20	20	L	8.50	1125	315	154/151	830	4000	3650	17.0
12.00R24	20	K	8.50	1126	315	160/157	900	4500	4125	15.5





GM906

▸ MIXED ROAD ▸ ON/OFF



PATTERN CHARACTERISTIC

- Tough blocks provide excellent traction and off-road performance throughout the life of the tyre;
- Special pattern design improve the self-cleaning performance;
- Deep grooves provide long tread life;
- Strong,solid shoulders give excellent stability and handling.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	14	M	8.25	1050	279	144/142	720	2800	2650	20.5
11R22.5	16	M	8.25	1050	279	146/143	830	3000	2725	20.5



GM907

▸ HIGHWAY ▸ ON/OFF ▸ REGIONAL



PATTERN CHARACTERISTIC

- Tough blocks,Provide excellent traction and off-road performance throughout the life of the tyre;
- Special pattern design,Effectively improve the self-cleaning performance;
- Deep grooves,Provide long tread life;
- Strong,solid shoulders,Give excellent stability and handling.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	16	M	8.25	1055	273	146/143	830	3000	2725	18.5
12R22.5	16	M	9.00	1084	300	150/147	850	3350	3150	19.0
12R22.5	18	M	9.00	1084	300	152/149	930	3550	3150	19.0
13R22.5	18	M	9.75	1124	320	154/151	875	4000	3350	18.0



GM916

▸ HIGHWAY



PATTERN CHARACTERISTIC

- Five broken-line grooves provide good traction, linear ride properties & stable steering;
- Unique inner-liner compound and bead design provide excellent durability;
- Full-width working plies provide a flat footprint for exceptional stability.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
315/80R22.5	18	M	9.00	1074	314	154/151	825	3750	3350	14.5
315/80R22.5	20	L	9.00	1074	314	154/151	850	4000	3350	14.5



GM917

▸ HIGHWAY ▸ REGIONAL



PATTERN CHARACTERISTIC

- Good sideslip and mud slip resistance;
- Suitable for guiding and all use.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R24.5	14	M	8.25	1092	279	146/143	720	3000	2725	11.5
11R24.5	16	M	8.30	1092	279	149/146	830	3250	3000	11.5
285/75R24.5	14	M	8.30	1053	283	144/141	760	2800	2575	12.0
285/75R24.5	16	M	8.30	1053	283	147/144	830	3075	2800	12.0
295/75R22.5	14	M	9.00	1014	298	144/141	760	2800	2575	11.5
295/75R22.5	16	M	9.00	1014	298	146/143	830	3000	2725	11.5



SmartWay℠



GM919

▸ MIXED ROAD ▸ ON/OFF



PATTERN CHARACTERISTIC

•The superior drive tyre for long distance highway and regional use;
•Deep block tread provide minimum wear and long original tread life;
•Wide base and deep groove provide good resistance to irregular wear & heat generation.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	14	K	8.25	1059	292	144/142	720	2800	2650	20.5
11R22.5	16	K	8.25	1059	292	146/143	830	3000	2725	20.5
11R24.5	14	K	8.25	1107	292	146/143	720	3000	2725	20.5
11R24.5	16	K	8.25	1107	292	149/146	830	3250	3000	20.5
285/75R24.5	14	K	8.25	1058	288	144/141	760	2800	2575	20.5
285/75R24.5	16	K	8.25	1058	288	147/144	830	3075	2800	20.5
295/75R22.5	14	K	9.00	1023	288	144/141	760	2800	2575	20.5
295/75R22.5	16	K	9.00	1023	288	146/143	830	3000	2725	20.5



GM928

▸ MINING ▸ ON/OFF ▸ MIXED ROAD



PATTERN CHARACTERISTIC


•Super driving and breaking performance;
•Good wear-resistance alibility.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
7.00R16LT	14	K	5.50F	775	200	118/114	770	1320	1180	14.5
7.50R16LT	14	L	6.0G	808	215	122/118	770	1500	1320	15.0
8.25R16	16	L	6.50H	858	235	128/124	770	1800	1600	16.0
9.00R20	16	K	7.00	1022	260	144/142	900	2800	2650	17.5
10.00R20	18	K	7.50	1054	278	149/146	930	3250	3000	19.0
11.00R20	18	K	8.00	1085	293	152/149	930	3550	3250	19.5
12.00R20	20	K	8.50	1127	310	156/153	900	4000	3650	21.5



GM936

▸ HIGHWAY ▸ URBAN



PATTERN CHARACTERISTIC

•Unique belt structure offers toughness to help deliver long tire life;
•Stable tread with cool running compound helps generate reduced squirm and lower heat;
•Barrel-shaped footprint & five-rib design offer even wear, many miles to removal and a low cost;
•Multi-siping helps deliver dependable grip and long, even wear.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	14	M	8.25	1050	279	144/142	720	2800	2650	14.5
11R22.5	16	M	8.25	1050	279	146/143	830	3000	2725	14.5



GM939

▸ HIGHWAY ▸ REGIONAL



PATTERN CHARACTERISTIC

•Wide and deep tread design provide extended tread life;
•Special tread pattern delivers a smooth and consistent wear;
•Uniform blog & lug design provide efficient traction on wet and dry roads.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
12R22.5	16	M	9.00	1084	300	152/148	850	3550	3150	14.5
295/80R22.5	16	M	9.00	1044	298	150/146	800	3350	3000	14.5
295/80R22.5	18	M	9.00	1044	298	152/148	850	3550	3150	14.5
315/80R22.5	18	M	9.00	1076	312	154/150	825	3750	3350	14.5
315/80R22.5	20	M	9.00	1076	312	156/150	850	4000	3350	14.5





GM957

▸ MIXED ROAD ▸ ON/OFF





PATTERN CHARACTERISTIC

- Special rubber compound designed for varied applications;
- Reinforced crown ply to improve resistance against oxidation;
- Excellent resistance to damage and punctures on/off road;
- Broad, directional block tread provide good on/off road grip.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
295/80R22.5	16	M	9.00	1044	298	150/146	800	3350	3000	21.5
295/80R22.5	18	M	9.00	1044	298	152/148	850	3550	3150	21.5
315/80R22.5	18	M	9.00	1076	312	154/150	825	3750	3350	21.5
315/80R22.5	20	M	9.00	1076	312	156/150	850	4000	3350	21.5
13R22.5	16	L	9.75	1124	320	154/150	850	3750	3350	21.5
13R22.5	18	K	9.75	1124	320	156/150	875	4000	3350	21.5

GM959

▸ ON/OFF ▸ REGIONAL





PATTERN CHARACTERISTIC

- Aggressive tread pattern with high resistance to cut and chipping;
- Extra deep tread insures long life.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
12.00R24	18	K	8.50	1226	315	158/155	830	4250	3875	21.0
12.00R24	20	K	8.50	1226	315	160/157	900	4500	4125	21.0

GM966

▸ HIGHWAY ▸ URBAN





PATTERN CHARACTERISTIC

- Five rib treade design for steer axles and highway usage;
- Reinforced steel cap piles for proving grabbing and anti slippery;
- High intensity tread enhancing long mileage;
- Wide shoulder helps reducing speed of abrasion.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
11R22.5	16	M	8.25	1054	279	146/143	830	3000	2725	14.5
11R24.5	16	M	8.25	1104	279	149/146	830	3250	3000	14.5
295/80R22.5	18	M	9.00	1044	298	152/149	900	3550	3250	15.5
295/75R22.5	16	M	9.00	1014	298	146/143	830	3000	2725	14.5

GM967

▸ HIGHWAY ▸ ON/OFF ▸ URBAN





PATTERN CHARACTERISTIC

- Specific tread compound enable lower heating,wear resistance and fuel economy;
- Extended road mileage;
- Ultra-high tire bead structure ensure excellent high speed and durability.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
295/80R22.5	16	M	9.00	1044	298	150/146	800	3350	3000	19.0
295/80R22.5	18	M	9.00	1044	298	152/148	850	3550	3150	19.0

GM969

▸ HIGHWAY ▸ REGIONAL





PATTERN CHARACTERISTIC

- Wide and deep tread design provide extended tread life;
- Special tread pattern delivers a smooth and consistent wear;
- Uniform blog & lug design provide efficient traction on wet and dry roads.

Size	P.R	Speed Rating	Standard Rim	Overall Diameter	Section width	Load Index	Relative Pressure Kpa	Max Tire Load/Kg		Tread Depth (mm)
				mm	mm			Single	Dual	
295/80R22.5	18	M	9.00	1050	292	152/149	900	3550	3250	19.5
315/70R22.5	16	M	9.00	1014	312	152/148	900	3550	3150	19.5
315/70R22.5	18	M	9.00	1014	312	154/150	900	3750	3350	19.5
315/80R22.5	20	L	9.00	1087	310	156/150	850	4000	3550	19.5



OTR TIRES



E3/L3

• BEST

SIZE	TYPE	PR	STANDARD RIM	TREAD DEPTH	S.W.	O.D.	Max Load(kg)		Max Pressure(kpa)	
					mm	mm	10km/h	50km/h	10km/h	50km/h
750-16	TT	16	6	12	185	761	1180		630	
825-16	TT	16	6.5	16	235	855	1800		730	
900-16	TT	16	6.5	16	255	890	1955		630	
10.00-16	TT	16	6.5	16	275	910	2742		565	
11.00-16	TT	16	6.5	16	293	1105	3135		650	
12.00-16	TT	16	6.5	16	325	1145	3585		750	
16/70-16	TT	12	8.50H	16	320	850	1955		390	
16/70-20	TT	20	13	21	410	1075	5150	2900	450	350
16/70-24	TT	14	13	23	410	1175	5600		450	
16.00-24	TT/TL	20	11.25/2.0	26	430	1490	9434	5340	578.5	422.75
	TT/TL	24	11.25/2.0	26	430	1490	10600	6000	650	475
16.00-25	TT/TL	28	11.25/2.0	29	430	1495	10600	6000	650	475
15.5-25	TT/TL	16	12.00/1.3	24.5	395	1275	6150	3750	475	325
	TT/TL	20	12.00/1.3		395	1275	6800	3850	460	285
17.5-25	TT/TL	16	14.00/1.5	28	445	1350	7300	4250	475	300
	TT/TL	20	14.00/1.5		445	1350	8250	5000	575	400
18.00-25	TT/TL	28	13.00/2.5	34	500	1615	13600	8000	650	500
	TT/TL	32	13.00/2.5		500	1615	15000	8750	750	575
	TT/TL	36	13.00/2.5		500	1615	16000	9250	850	625
	TT/TL	40	13.00/2.5		500	1615	17000	9750	950	700
20.5-25	TT/TL	20	17.00/2.0	30	520	1490	8835	5580	420	304
	TT/TL	24	17.00/2.0		520	1490	9500	6000	450	325
23.5-25	TT/TL	20	19.50/2.5	33	595	1615	10900	7300	375	300
	TT/TL	24	19.50/2.5		595	1615	12500	8000	475	300
26.5-25	TT/TL	24	22.00/3.0	34	675	1750	13500	9132	385	325
	TT/TL	28	22.00/3.0		675	1750	15500	10000	475	350
	TT/TL	32	22.00/3.0		675	1750	16275	10500	498	367
	TT/TL	36	22.00/3.0		675	1750	17089	11025	523	385
29.5-25	TT/TL	28	25.00/3.6	38	750	1923	17500	11500	425	325



L3 NEW

• BEST

SIZE	TYPE	PR	STANDARD RIM	TREAD DEPTH	S.W.	O.D.	LOADING	PRESSURE
					mm	mm	Kg	Kpa
16/70-16	TT	14	10	16	353	915	1600	390
20.5/70-16	TT	14	10	16	353	915	1600	390
23.5/70-16	TT	14	8.5	16	410	1075	1600	390
17.5-25	TT/TL	16	14	26	445	1350	7300	475
20.5-25	TT/TL	20	17	30	520	1490	9500	450
23.5-25	TT/TL	24	19.5	33	595	1615	12500	475
26.5-25	TT/TL	28	22	35	675	1750	15500	475



E-3A

• BEST

SIZE	TYPE	PR	STANDARD RIM	TREAD DEPTH	S.W.	O.D.	LOADING	PRESSURE
					mm	mm	Kg	Kpa
14.00-20	TT	28	10	20	375	1265	5600	930



E4

• BEST

SIZE	TYPE	PR	STANDARD RIM	TREAD DEPTH	S.W.	O.D.	LOADING	PRESSURE
					mm	mm	Kg	Kpa
12.00-24	TT/TL	28	8.5	46	315	1245	9900	950
14.00-24	TT/TL	36	10	46	375	1370	16200	1100



•BEST

SIZE	TYPE	PR	STANDARD RIM	TREAD DEPTH	S.W.	O.D.	LOADING	PRESSURE
					mm	mm	Kg	Kpa
9.00-20	TT	16	7	--	255	1015	4000	625
11.00-20	TT	16	8	--	290	1080	5450	725
10.00-20	TT	16	7.5	--	278	1055	3260	670

C1



•BEST

SIZE	TYPE	PR	STANDARD RIM	TREAD DEPTH	S.W.	O.D.	LOADING	PRESSURE
					mm	mm	Kg	Kpa
23.1-26	TT/TL	16	DW20	16	595	1500	5600	230

C2



SIZE	11R22.5	11R24.5	12R22.5	13R22.5	215/75R17.5	225/70R19.5	235/75R17.5	245/70R19.5	265/70R19.5	275/70R22.5	275/80R22.5	285/75R24.5	295/75R22.5
GM138	●		●										
GM158													
GM168													
GM512	●	●			●	●	●	●	●	●		●	●
GM522	●	●										●	●
GM562	●		●								●		
GM563			●										
GM565			●										
GM566													
GM578	●		●		●	●	●	●	●		●		
GM582													
GM583													
GM585													
GM586													
GM626													
GM628													
GM698													
GM712													
GM788													
GM826	●												
GM836													
GM859													
GM869			●										
GM901	●	●	●	●									
GM902													
GM903													
GM906	●												
GM907	●		●	●									
GM916													
GM917		●										●	●
GM919	●	●										●	●
GM928													
GM936	●												
GM939			●										
GM957				●									
GM959													
GM966	●	●											●
GM967													
GM969													